

VZ SEAL BAND

Cold self-adhesive band

DESCRIPTION

Cold self-adhesive band made of butyl mastic covered with non-woven mat. The non-woven mat allows the product strain. The adhesive side is protected by a peeling support.

CHARACTERISTICS

Sealing of under tile floor-wall connection. The non-woven mat adapts to the surface shape and can be covered by tiles glue or other coatings or paint. Joints waterproofing. Repairing of cement or asbestos cement cracks.

SURFACE PREPARATION

It is the user's duty to verify the mastic compatibility with the different supports in terms of adherence as well as the chemical compatibility. The supports must be clean, dry and without dust.

ADVICES

Do not add any additive .
Do not use if the drum is damaged.

APPLICATION

Remove protective layer, place band on the support avoiding the formations of air pockets between the butyl and the support. In case of joints, overlap the products at least 5 cm.

The non-woven mat can be painted again. However it is to be noted that, due to the extreme flexibility of the butyl mastic , the layer of paint which covers the non-woven mat can show some small cracks. The coatings, glues or paints which covers the non-woven mat must be compatible with this last one. The butyl mastic is sensible to solvents.

WARNINGS

Before application we advice to repair any possible surface irregularities, to glue possible detached tiles and verify the presence of occluded humidity to avoid the formation of vapour.

Avoid using if rain is imminent or on wet surfaces.

Do not apply any concrete mix over it before IDROVAL ELASTIC has completely dried.

PACKAGING

Roll: 80 mm x 10 m

Colour

Non-woven mat: white
Butyl: grey

STORAGE

Product will last for 12 months from production date, with the closed original package. Store in a ventilated room away from dampness and at a maximum temperature of 30°C.

The storage to a temperature higher than 30°C can cause some difficulties on the releasing of the silicone paper from the butyl during application.

VZ SEAL BAND

Cold self-adhesive band

SAFETY NORMS

PRECAUTIONS

For information on safety norms, the user will have to refer to the most recent Safety Data Sheet, drawn to comply to the current regulations, containing the physical, toxicological and various other data concerning the used product.

ECOLOGY

Do not waste the product or the empty drums in the environment. Refer to the most recent Safety Data Sheet for further information on possible disposal methods.

TECHNICAL DATA (medium values) PRODUCT FOR PROFESSIONAL USERS

COVERING IN NON-WOVEN MAT

Nature:		100% polypropilene
m ² Mass	D 45 1012	50 g/m ²
Tensile Strength	Machine direction	90 N/5 cm
	Transversal direction	65 N/5 cm
Water repellent		Yes

BUTYL ADHESIVE MASTIC

Dry residue		> 99%
Resistance to drop	Butyl at 5°C ISO 7390	≤ 3 mm
	Butyl at 70°C ISO 7390	≤ 3 mm
Behaviour at -30° C.	D 421313	No detachment
Resistance to drip	Warm method with	
perforated plate D 45 5256	No drip	
Peeling at 90°	On steel MEL 052	≥ 4 N/cm
Temperature	Laying temperature	+5°C ≤ T ≤ +40°C
	Working interval	+30°C ≤ T ≤ +80°C

Product conforming to the rules of Directive 2003/53/CE

Rev. 1 - 03/10