## **Gummiflex PL N20**

Dimension	Gummiflex N20	3PL	4PL	5PL	
Method of application	Fully torch applied				
	Reinforcement: Polyester reinforced with fiber glass				
	Back Surface: Film				
Composition	Top Surface: Fine sand	1			
Certifications and Agreements	CE marking - FPC certif	icate number 137	0-CPR-0042.	IM PL	
Field of use	Exposed not-accessible roofs, technical roofs exposed or under heavy protection, roofs accessible to pedestrian. Foundation waterproofing works.				
CE	Base layer for multi-lawith EN13707 for flawaterproofing works acc	t roofs. Layer fo	or foundation	Ø, Val	
Description	APP modified bitumen membrane. This product is designed for both new roofing works and refurbishment works. This product is also approved for foundation waterproofing works.				





and packaging

Thickness (mm)

Weight (kg/m2)

Rolls (m)

4,0

1x10

5,0

1x10

3,0

1x10

Property	Test Method	Unit	Value	Tollerance		
Lenght	EN 1848-1	m	10	-1%		
Width	EN 1848-1	m	1,0	-1%		
Thickness	EN 1849-1	mm	3,0 / 4,0 / 5,0	±0,2		
Weight	EN 1849-1	Kg/m2	NPD	±10%		
Tensile strength at max	EN 12 311-1	L x T (N/50mm)	500/350	-20%		
Elongation at max	EN 12 311-1	L x T (%)	30/30	-15		
Nail tearing resistance	EN 12 310-1	LxT(N)	130/130	-30%		
Static load	EN 12 730	Kg	10	2		
Resistance to impact	EN 12691	mm	800	≥		
Joints Shear resistance	EN 12317-1	N / 50mm	500/350	-20%		
Flexibility at low temperature	EN 1109	(°C)	-10	≤		
Flow resistance at elevated temperature	EN 1110	(°C)	120	≥		
Dimensional stability	EN 1107-1	%	±0,3	≤		
Watertightness	EN 1928-B	kPa	60	≥		
Vapour Transmission (μ)	EN 1931	-	20000	≥		
Reaction to fire	EN 13501-1	-	E	-		
External fire performance	EN 13501-5	-	Froof	-		
Storage	This product is packaged in rolls set up vertically on pallet or wooden box. It must be stored vertically under shelter, away from heat sources.					
Modifications	Our company reserves the right to modify its composition as a result of technologic and experiments improvements. This product data sheet supersedes the previous edition, to obtain the updated technical data sheet, please contact our technical department.					



www.vallizabban.it

