

DECLARATION OF PERFORMANCE: 11140245-5

1. Identification Code: 11140245 ELASTOGUM 5 PL SUPER 33

2. Intended use:

Standard: EN	Intended use:
13707:2013	Reinforced flexible bitumen sheets for roof waterproofing:
	Single layer
	Top layer
	X Underlay and intermediate layer
	X Layer under heavy protection
	Layer for roof gardens
13969:2007	X Bitumen damp proof sheets including bitumen basement tanking sheets
13859-1:2014	Flexible sheets for waterproofing : Underlays for discontinuous roofing
13970:2007	Bitumen water vapour control layers
14695:2010	X Reinforced bitumen sheets for waterproofing concrete bridge decks and other areas of concrete subject to traffic

3. Manufacturer: Valli Zabban S.p.A - 50041 Calenzano (FI) - Via Di Le Prata, 103 - Tel +39 055 328041 - Fax +39 055 300 300 www.vallizabban.it - info@vallizabban.it

4. System or systems of assessment and verification of constancy of performance of the construction product:

EN harmonized standard	VVCP systems
13707 / 13969 / 14695	System 2+
13859-1 / 13970	System 3

5. Notified bodies:

EN harmonized standard	Notified body / laboratory	Notification code	FPC Certificate of conformity
13707 / 13969 / 14695	Bureau Veritas	1370	1370-CPR-0042
13859-1	Technische Universität München	1211	/
13970	Technische Universität München	1211	/

6. Declared performances:

Relevant characteristics :	Unit	Performance	Tolerance ⁽¹⁾	EN Test	EN harmonized standard				
					13707	13969	14695	13970	13859-1
External Fire Performance	Broof	F roof	-	13501-5	●				
Reaction To Fire	Classe	F	-	13501-1	●	●		●	●
Watertightness	kPa	500	≥	1928	●	●		●	
Watertightness	Classe	NPD	-						●
Tensile strength at max L/T	N/5cm	1200 / 1200	±20%	12311-1	●	●	●	●	●
Elongation at max L/T	%	50 / 50	± 15						
Root resistance		NPD	-	13948	●				
Resistance to static loading – Method A soft substrate	Kg	NPD	≥	12730	●				
Resistance to static loading – Method B hard substrate	Kg	35	≥	12730	●	●			
Resistance to impact – Method B soft substrate	mm	NPD	≥	12691	●				
Resistance to impact - Method A hard substrate	mm	2000	≥	12691	●	●		●	
Nail tearing resistance L/T	N	250 / 250	±30%	12310-1	●	●		●	●
Peel resistance of joints	N/5cm	40	-20	12316-1	●				
Shear resistance of joints	N/5cm	850 / 820	±20%	12317-1	●	●		●	
Flexibility at low temperature	°C	- 20	≤	1109	●	●	●	●	●
Vapour resistance	μ	20000	≥	1931				●	
Durability after ageing T: Flexibility at low temperature	°C	NPD	≤	1296 / 1109	●		●		
Durability after ageing T: Flow resistance at elevated temperature	°C	90	-10	1296 / 1110					
Durability after ageing UV: Visible difects		NPD	-	1297 / 1850-1	●				
Durability after ageing UV/T: Tensile strength at max L/T	N/5cm	NPD	-	1297 / 1296 / 12311-1					●
Durability after ageing UV/T: Elongation at max L/T	%	NPD	-						
Durability after ageing UV/T: Watertightness	kPa	Passa/passed	-	1297 / 1296 / 1928					
Durability after ageing T: Watertightness	kPa	Passa/Passed	-	1296 / 1928		●			
Durability after ageing RC: Watertightness	kPa	NPD	-	1847 / 1928					
Durability after ageing T: Vapour resistance	μ	NPD	-	1296 / 1931				●	
Durability after ageing RC: Vapour resistance	μ	NPD	-	1847 / 1931					
Water absorption	%	1,5	≤	14223					
Watertightness	kPa	500	≥	14694					
Bond strength	N/mm²	0,7	≥	13596					
Crack bridging	°C	NPD	-	14224					
Compatibility by heat conditioning	%	NPD	-	14691			●		
Resistance to thermal shock	%	NPD	-	14693					
Resistance to compaction of an asphalt layer		Passa/Passed	≥	14692					
Shear strength	N/mm²	0,15	≥	13653					
Dangerous substances	This Product does not contain asbestos or tar constituents. ⁽²⁾				●	●	●	●	●

(1) Note: In the absence of a uniform test method throughout Europe, any verifications and declarations on release/content must be performed considering the national regulations of the place of use.

7. The performance of the product identified in points 1 and 2 id in conformity with the declared performance in point 7. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Place and date of issue Calenzano , Italy 05/06/2024

Responsabile Tecnico Daniele Piccardi